



FDRM

**Product description:**

FDRM is a sealing ring for metric threads, available in grey.

This sealing ring is used for all threaded connectors and reducers with metric threads.

Temperature resistance range: -45° C to +150° C



Cat. No.:	Type	Inside Ø mm	Outside Ø mm	Content	PU	Weight PU/kg	Overall height mm	Thread
288 90 016	16	16,2	22,3	100	PCS	0,100	2,0	M16x1,5
288 90 020	20	20,5	25,9	100	PCS	0,100	2,0	M20x1,5
288 90 025	25	25,4	31,8	50	PCS	0,050	2,0	M25x1,5
288 90 032	32	32,4	39,1	50	PCS	0,050	2,0	M32x1,5
288 90 040	40	40,4	49,8	20	PCS	0,040	2,0	M40x1,5
288 90 050	50	50,3	59,7	25	PCS	0,075	2,0	M50x1,5
288 90 063	63	63,3	72,4	25	PCS	0,075	2,0	M63x1,5

All dimensions without tolerances are for information only.



FDRM

Fields of application

on plaster	machines	•
under plaster	hot asphalt	
on wood	under screed	
underground installation	prefabricated construction	
in concrete	outdoor	

Hotline

Since technical developments cannot be foreseen, electrical installations should provide the possibility to be expanded at any time.

Information can be obtained from our technical consultants at +49 9525 88-8123